

LISTING OF CLAIMS

1. (currently amended) An eluter instrument for an SPE system, comprising:

(a) a housing for an eluter instrument;

(b) an upper seal mounted in said housing with apparatus for moving said upper seal in up and down motion with respect to said housing;

(c) a lower seal mounted in said housing with apparatus for moving said ~~upper~~ lower seal in up and down motion with respect to said housing;

(d) an SPE medium disposed between said upper seal and said lower seal;
and

(e) said upper seal and said lower seal being moveable between a first position in which said upper seal and said lower seal are spaced apart and not in proximity and a second position in which said upper seal and said lower seal are in proximity and spaced apart sufficiently only to clamp therebetween a first area of a plurality of areas of an SPE medium, said first area containing therein one or more compounds of interest, ~~such as~~;

(f) apparatus to [permit elution of] elute said one or more compounds of interest sequentially from said plurality of areas to another, single instrument;
and

(g) apparatus to introduce said SPE medium to and remove said SPE medium from a treatment area of said eluter instrument.

2. (original) An eluter instrument for an SPE system, as defined in Claim 1, wherein: said upper seal and said lower seal are O-rings.

3. (original) An eluter instrument for an SPE system, as defined in Claim 1, wherein: said upper seal and said lower seal engage surfaces of a dam formed around said first area.

4. (original) An eluter instrument for an SPE system, as defined in Claim 3, wherein: said dam is formed by heat-sealing a portion of said SPE medium.

5. (original) An eluter instrument for an SPE system, as defined in Claim 1, further comprising: apparatus to automatically move said SPE medium and clamp a second area of said SPE medium between said upper seal and said lower seal.

6. (original) An eluter instrument for an SPE system, as defined in Claim 5, wherein: said apparatus includes first and second stackers for stacking a plurality of frames containing a plurality of SPE media such that said frames can be fed in and out of an elution station automatically without operator handling.

7. (original) An eluter instrument for an SPE system, as defined in Claim 1, further comprising: a first frit disposed above said first seal and a second frit disposed below said second seal, said first frit and said second frit to distribute eluent solvent across said first area.

8. (original) An eluter instrument for an SPE system, as defined in Claim 6, further comprising: means for reading identifying indicia on said frames, combined with software, to generate a data audit trail of each incoming said frame, with processing parameters for each frame contained in said identifying indicia.

9. (currently amended) An eluter instrument for an SPE system, comprising:

(a) a housing for an eluter instrument;

(b) a plurality of upper seals mounted in said housing with apparatus for moving said upper seals in up and down motion with respect to said housing;

(c) a plurality of lower seals mounted in said housing with apparatus for moving said lower seals in up and down motion with respect thereto;

(d) said upper seals and said lower seals being moveable between a first position in which said upper seals and said lower seals are spaced apart and not in proximity and a second position in which said upper seals and said lower seals are in proximity and spaced apart sufficiently only to clamp therebetween a plurality of areas of an SPE medium, said plurality of areas containing therein one or more compounds of interest, ~~such as; and~~

(e) apparatus to [permit elution of] elute said one or more compounds of interest sequentially from said plurality of areas to another, single instrument;

~~(e)~~ (f) valving to selectively and sequentially select one of said plurality of areas from which to elute said one or more compounds of interest; and

(g) apparatus to introduce said SPE medium to and remove said SPE medium from a treatment area of said eluter instrument.

10. (original) An eluter instrument for an SPE system, as defined in Claim 9, wherein: said valving is automatically controlled to select one of said plurality of areas from which to elute said one or more compounds of interest.

AMENDMENT
S/N 09/752,272, FILED 01/02/01

PATENT
130-132

AMENDMENTS TO THE SPECIFICATION

None.

AMENDMENT
S/N 09/752,272, FILED 01/02/01

PATENT
130-132

AMENDMENTS TO DRAWING FIGURES

Please substitute the enclosed drawing figures for the drawing figures filed with the application.

AMENDMENT
S/N 09/752,272, FILED 01/02/01

PATENT
130-132

REMARKS

The above-referenced Office Action has been carefully reviewed and reconsideration thereof is respectfully requested.

Claims 1-10 have been rejected under 35 USC 112, second paragraph, as being indefinite. The Examiner's suggestions have been adopted and it is believed that the above amendments to Claims 1 and 9 fully overcome this ground of rejection.


A set of formal drawings to be filed in the present application is submitted herewith. No new material has been inserted in the drawings.

In view of the above amendments and remarks, it is respectfully submitted that the claims in the application, Claims 1-10 are allowable and early action in that regard is respectfully requested.

Should the Examiner have any questions as to the allowability of the claims or have any suggestions with respect to the wording thereof, the undersigned would be grateful for the privilege of a telephone conference with the Examiner.

Date: August 7, 2003.

Respectfully submitted,



John H. Crozier
Reg. No. 30,371
1934 Huntington Turnpike
Trumbull CT 06611-5116
Tel: (203) 375-9118
Fax: (203) 378-8108